









honey



dark

VINTAGE

GLAZED PORCELAIN

6"x36"

- 1096283 - cream
- 1096284 - gray
- 1096285 - honey
- 1096286 - dark



SHADE VARIATION



V1

UNIFORM APPEARANCE
Differences among pieces from the same production run are minimal.



V2

SLIGHT VARIATION
Clearly distinguishable differences in texture and/or pattern with similar colors.



V3

MODERATE VARIATION
While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece will vary significantly.



V4

SUBSTANTIAL VARIATION
Random color differences from tile to tile, so that one tile may have totally different colors from that on other tiles. Thus, the final installation will be unique.

★ CONSUMERS SHOULD LOOK AT MULTIPLE PIECES OF TILE TO REALIZE THE FULL COLOR SPECTRUM OF THIS PRODUCT.

PACKAGING SPECIFICATIONS

SIZE	METRIC (CM)	SF/CTN	PIECES/CTN	CT/PALLET	UM/PALLET	WEIGHT (LBS)/ CTN	WEIGHT (LBS)/ PALLET
6"x36"	15x90	12	8	44	528	55.2	528

ALL OTHER SIZES WILL BE PACKAGED AS ORDERED.

MINIMUM GROUT SIZE RECOMMENDED = 5MM (OR APPROX. 1/8"). IF STAGGERED TILE PLACEMENT, WE RECOMMEND USING 30% OFFSET. IF SPECIFIED BRICK PATTERN WITH 1/2 PATTERN MANDATORY, A BIGGER GROUT IS RECOMMENDED TO HIDE IMPERFECTIONS OF INSTALLATION (MINIMUM 3/16")

TECHNICAL SPECIFICATIONS

Thickness	10mm	
Shade Variation	V3	
Surface Abrasion	PEIIV	ASTM C1027
Water Absorption	≤ 0.5%	ASTM C373
Chemical Resistance	NOT AFFECTED	ASTM 650
Dynamic Coefficient of Friction	≥ 0.50 ◆	ANSI 137.1
Stain Resistance	NOT AFFECTED	ASTM C1378
Breaking Strength	≥ .400	ASTM C648
Resistance to Freeze	RESISTANT	ASTM C1026
Scratch Hardness	≥ 7	MOHS

PRODUCTS MEET OR EXCEED ALL STANDARDS IN ANSI A137.1.

◆ DUE TO THE INHERENT NATURE OF FIRED PORCELAIN TILE, IT IS IMPORTANT TO NOTE THAT THE COEFFICIENT OF FRICTION MAY VARY WITHIN AND BETWEEN PRODUCT RUNS.